


Technical description


1. Dimensions / Weight



CASHY SPECIAL
SWIVEL CHAIR 5A



CASHY SPECIAL
SWIVEL CHAIR 5A RB



CASHY SPECIAL
SWIVEL CHAIR 4S



| Model | Dimensions (mm) | | | | | | | | | | | | | | | Weight (kg) |
|----------------------------------|-----------------|---------|-----|-----|-----|-----------|-----|-----|-----|-----|-----|-----|---|---|---|-------------|
| | A | A1 | B | C | D | E | F | G | H | J | K | L | I | M | N | |
| CASHY SPECIAL SWIVEL CHAIR 5A | 390–520 | 380–510 | 440 | 455 | 460 | 820–945 | 420 | 320 | 430 | 710 | 710 | 644 | — | — | — | 8,6 |
| CASHY SPECIAL SWIVEL CHAIR 5A RB | 590–815 | 570–795 | 440 | 455 | 460 | 1000–1250 | 420 | 320 | 430 | 710 | 710 | 694 | — | — | — | 10,2 |
| CASHY SPECIAL SWIVEL CHAIR 4S | 425 | — | 440 | 455 | 460 | 850 | 420 | 320 | 430 | — | 676 | 676 | — | — | — | 6,8 |

A – Seat height

A1 – Seat height according to standard EN

B – Seat depth

C – Seat surface depth

D – Seat width

E – Overall height

F – Backrest width

G – Backrest length

H – Backrest height

J – Base diameter

K – Base width

L – Overall depth

I – Headrest height (above the backrest)

M – Headrest width

N – Headrest height



| Armrests | Dimensions (mm) | | | | | Weight (kg) |
|----------|-----------------|-----|----|-----|-----|-------------|
| | Z | Y | X | W | V | |
| GTP62 | 240 | 235 | 75 | 470 | 620 | 1,2 |

Z – Armrest height

Y – Armrest length

X – Armrest width

W – Internal width between armrests

V – External width between armrests

2. Materials / Versions

2.1. Base

Bases:

- Ø 710 mm five-star black polyamide (TS25),
- Ø 676 mm four-star black polyamide (TS37).

Footrest – ring base Ø 456 mm, made of black glass fiber reinforced polyamide (PA + GF).

Height adjustable with a knob.

2.2. Castors / Glides

2.2.1. Special swivel chairs

Ø 50 mm black plastic self-braking castors for soft floors (SH50) as standard, or hard floors (SHH50) as an option – applies to TS25 base.

Glides for soft floors, with felt option for hard floors (GD-SPHF) – applies to TS37 base.

2.2.2. Special swivel chair with footrest

Glides for soft floors (GB) as standard.

Ø 50 mm load-brake castors for soft floors (KSH) or hard floors (KSHH) – both as an option.

2.3. Mechanisms

PST45-BL swivel mechanism with height adjustment – applies to TS25 base.

MP13 swivel mechanism – applies to TS37 base.

2.4. Seat, backrest

Seat with cover

Seat cover integrated with backrest connector, made of glass fiber reinforced polyamide (PA + GF) in black or grey colour.

Seat made of glass fiber reinforced polypropylene (PP + GF) in black, grey, red or blue colour.

Backrest

Backrest made of glass fiber reinforced polypropylene (PP + GF) in black, grey, red or blue colour.

3. Armrests

Fixed armrests – made of black glass fiber reinforced polyamide (PA + GF) applies to TS25 base.

4. Packaging

Special swivel chair with five-star base

Partially assembled, cardboard packaging

(PACK-A), 1 piece per box, 8 pieces on pallet.

The box contains 4 separate elements:

- seat with assembled mechanism and backrest,
- armrests,
- base with assembled castors,
- pneumatic gas lift.

Special swivel chair with five-star base and footrest

Partially assembled, cardboard packaging

(PACK-A), 1 piece per box, 8 pieces on pallet.

The box contains 5 separate elements:

- seat with assembled mechanism and backrest,
- base with assembled glides,
- armrests,
- pneumatic gas lift,
- footrest.

Special swivel chair with four-star base

Assembled, cardboard packaging (PACK-ASM),

1 piece per box, 8 pieces on pallet.

5. Technical regulations, approvals and quality marks for the chairs (for selected product configurations)

Approval compliant with EN 1335 – pending.